



Material Safety Data Sheet

1. Product and Company Identification

Product CodeMTGS

Product Name....BRICKFORM® Micro-Topping-SG-gray™

ManufacturerBRICKFORM, A Division of Solomon Colors, Inc.

Address360 S Lilac Avenue

City, State, Zip....Rialto, CA 92376

Emergency Phone800-373-7542

Business Phone909-484-3399

Business Fax.....217-744-2605

Last UpdatedMay 14, 2012

2. Composition / Information on Ingredients

Chemical Name	CAS No.	ACGIH TLV	OSHA PEL	STEL
Portland Cement	65997-15-1	5 mg/m ³	10 mg/m ³	N/A
Calcium Carbonate	1317-65-3	10 mg/m ³	10 mg/m ³	N/A
Silicon Dioxide	14808-60-7	10 mg/m ³	10 mg/m ³	N/A

3. Hazards Identification

Emergency Overview

Gray, sandy powder.

Signs and Symptoms of Exposure

Ingestion

May cause Alkali burns of the mouth, throat, and gastrointestinal tract.

Inhalation

Prolonged exposure to dust may result in irritation to upper respiratory tract. Chronic lung injury can occur. Acute silicosis may develop in a short time with heavy exposure. Silicosis can be progressive and may cause death.

Eyes

May cause irritation, inflammation or abrasion.

Skin

Prolonged and repeated contact can cause abrading of the skin or defatting drying of the skin, which may result in skin irritation and dermatitis. Exposure to wet material can cause caustic burns.

Potential Environmental Hazards

N/A

4. First Aid Measures

Ingestion

DO NOT INDUCE VOMITING. Drink two glasses of water and GET MEDICAL ATTENTION IMMEDIATELY.

Inhalation

Remove victim to fresh air. If respiratory symptoms persist or develop, GET MEDICAL ATTENTION.

Eyes

DO NOT RUB. Flush eyes with plenty of water for 15 minutes while holding eyelids open. If irritation persists, GET MEDICAL ATTENTION IMMEDIATELY.

Skin

Wash with soap and water. Remove contaminated clothing and shoes. Do not reuse until cleaned. If irritation persists or caustic burns develop, GET MEDICAL ATTENTION.

continued

5. Fire Fighting Measures

Flash Point N/A

Autoignition Temperature N/A

Lower Explosive Limit N/A

Upper Explosive Limit N/A

Unusual Fire Explosion Hazards

N/A

Extinguishing Media

Product is not flammable. Use standard fire-fighting procedures without regard to product.

Special Fire Fighting Procedures

N/A

6. Accidental Release Measures

Keep people away. Vacuum, scoop, or broom-up spilled powders and place in containers. Avoid generation, exposure, and inhalation of dust. Collect spilled powders, place in non-leaking containers, seal tightly, and label properly. Dispose of in accordance with applicable local, county, state, and federal regulations.

7. Handling and Storage

Safe Handling and Storage

Keep containers closed. Store in a cool, dry place, away from acids and strong oxidants and moisture.

8. Exposure Controls and Personal Protection

Engineering controls

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup to dust in air.

Personal Protective Equipment

All personnel must wear OSHA-NIOSH approved dust respirators when working with or near this product. Please refer to OSHA standards in 29 CFR 1910.134. Wear safety goggles to protect eyes. Aprons and gloves should be worn to minimize contact with skin.

Other Protective Clothing Equipment

N/A

General Work Practices Hygiene Considerations

Minimize breathing of dust. Avoid prolonged or repeated contact with skin. Use good hygiene when handling this product. Cleanse skin thoroughly after handling and before eating or drinking. Product is easily removed with waterless, hand cleaners followed by washing thoroughly with soap and water. Remove contaminated clothing and launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse.

Exposure Guidelines

Please see section 2.

9. Physical and Chemical Properties

Physical State Powder

Melting Point/Range N/A

Solubility in Water slight

pH Alkaline when wet

Molecular Weight N/A

Vapor Pressure (mmHg) N/A

VOC N/A

Appearance/Color/Odor Gray/N/A

Boiling Point/Range N/A

How to Detect this Compound N/A

Specific Gravity (Water = 1) Approximately 2.9

Percent Volatiles N/A

Vapor Density (Air = 1) N/A

BRICKFORM

Material Safety Data Sheet

10. Stability and Reactivity

Stability Stable.
Hazardous Polymerization Will not occur.
Conditions To Avoid High humidity.
Materials To Avoid Oxidizers, acids and moisture.
Hazardous Decomposition Products Calcium Oxide.

11. Toxicological Information

N/A

12. Ecological Information

N/A

13. Disposal Considerations

Use non-leaking containers, seal tightly and label properly. Dispose of in accordance with applicable local, county, state, and federal guidelines. Do not dispose in streams, wells, lakes, rivers, oceans, or sewers.

14. Transportation Information

DOT Proper Shipping Name Dry Cement
DOT Hazard Class ID Number Non-hazardous. Not required. Class 55.

15. Regulatory Information

Reportable Quantity N/A

NFPA Rating 0=Insignificant, 1=Slight, 2=Moderate, 3=High, 4=Extreme

Health 2
Flammability 0
Reactivity 0

Carcinogenicity Lists Yes
NTP No
IARC Monograph Yes
OSHA Regulated Yes

STATE WARNING

California Prop 65: This product may contain a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
Many States have adopted Federal guidelines and restrictions for hazardous chemicals. A complete list is available at www.epa.gov/ceppo/pubs/title3.pdf. Some states have expanded the Federal List and you should check with your local regulatory agency for any additional restrictions on the hazardous chemicals listed in this section.

continued

15. Regulatory Information...continued

FEDERAL WARNING

Section 313 Supplier Notification: This product contains the following toxic chemical(s) subject to the reporting requirements of SARA TITLE III, Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

CAS#	CHEMICAL NAME	%BY WEIGHT
14808-60-7	Silicon Dioxide	10-25
65997-15-1	Portland Cement	10-25

16. Other Information

IMPORTANT! Read this MSDS before use or disposal of this product. Pass along the information to employees and any other persons who could be exposed to the product to be sure that they are aware of the information before use or other exposure.

This MSDS has been prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200). To the best of our knowledge, the information contained herein is accurate and the information is based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change, BRICKFORM makes no warranty, either expressed or implied with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. The data on this sheet is related only to this specific material. It may not be valid for this material if used in combination with any other materials. It is the user's responsibility to determine suitability and completeness of this information with regards to a particular use. Additional information may be necessary or helpful for specific conditions and circumstances of use. Unknown hazards may exist and this material should be used with caution. BRICKFORM assumes no legal responsibility for use or reliance upon this data.