



BRICKFORM® E-Etch™

Floor cleaner, degreaser and light etching product

PRODUCT DESCRIPTION • E-Etch is an environmentally friendly industrial strength floor cleaner, degreaser and light etching product. It is ideal for cleaning and preparing cementitious surfaces for acid staining, decorative overlays, water base stains, coatings application, etc. It may also be used on concrete, stucco, terrazzo and most masonry surfaces to open up the pores on the surface and clean grime, dirt, grease, scuff marks and stains. E-Etch will lightly etch most concrete slabs. E-Etch, when used to prepare slabs for acid staining, will have little to no effect on acid stain results. It is biodegradable and easily rinsed off with water.

USES

E-Etch degreases, removes food soils, soot, soap films, sludge, dirt, grime, laitance and other organic and inorganic soils.

- Effectively cleans and prepares floors for acid stain, overlays and sealer application
- Strong and versatile may be used for maintenance of industrial facilities, parking garages, airport runways, and loading docks
- Safer formula contains no Hydrochloric Acid
- May be used on interior or exterior slabs

FEATURES

- It is made with a biodegradable, naturally occurring solvent with an FDA-GRAS Rating (generally recognized as safe™). Its natural citrus-based enzyme solvents do not contain any harmful acids or petrochemicals.
- Safe to use in many different locations and sensitive areas such as: Restaurants, schools, hospitals, hotels, stadiums, malls, and food processing plants.
- Removes tough and stubborn materials and stains
- Made with natural ingredients
- Biodegradable
- Concentrated
- Pleasant smell
- Non-Acid
- Non-Caustic
- Non-Corrosive
- Non-Flammable
- Non-Hazardous
- Non-Abrasive
- Non-Carcinogenic

TECHNICAL DATA AND SPECIFICATIONS

Undiluted Coverage Rate	250 ft ² per gallon
VOC	Compliant
Color	Clear
Water Miscible	Yes
Biodegradable	Yes
Film Forming	No
Shelf Life	Over 2 years
Hazardous Solvents	No

APPLICATION

E-Etch is concentrated and can be diluted with water depending on the condition of the slab you are cleaning. Dilution rates up to one part E-Etch to one part water are acceptable. Apply material with sprayer, mop, sponge or medium stiffness broom. Allow to stand for 2-3 minutes and then scrub with a brush or a rotary floor scrubbing machine with a black pad or a zim grit brush. Rinse or pressure wash with clean water. Multiple applications may be needed for heavy duty cleaning or high dirt build up.

See product application videos at www.brickform.com.

ACID STAINING OR CEMENT OVERLAYS

To prepare floors for acid staining or overlays, BRICKFORM recommends using a floor scrubber with a pad. This will provide a deeper, more thorough cleaning, that will open the concrete pores and allow for deeper penetration of the stain, and better bonding of the sealer.

CLEANING

Clean and rinse equipment with clean water immediately after application.

LIMITATIONS

- Not for use on metal or any other surface that may be damaged by acidic products.
- Wear protective gloves and goggles during application.
- Neutralize floors prior of application of water base stains or sealers.
- E-Etch may not effectively etch tightly troweled, dense floors. Mock ups are recommended to determine if proper profiling can be achieved with E-Etch.

STORAGE

E-Etch should be stored between 32° and 100° F (0° to 38°C) in tightly sealed and original factory containers.

CAUTION

May cause eye and skin irritation, and may be harmful if swallowed. Avoid eye contact; in case of contact flush eyes with water for 15 minutes. If swallowed, do not induce vomiting, drink large amounts of water or milk and seek immediate medical attention. **KEEP AWAY FROM CHILDREN.**

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

MANUFACTURER

BRICKFORM, A Division of Solomon Colors, Inc.

ORDER SPECIFICATIONS

E-Etch		
Shipping Weight	Container Size	Item No.
10 lb	1 gallon	ES-1200