



BRICKFORM® Traction Grip™

Anti-Slip Additive

PRODUCT DESCRIPTION

Traction Grip™ is an anti-slip micronized powder that adds texture to Decorative Sealers (BRICKFORM Gem-Seal, Gem Cure & Seal, Poly-Seal, and Satin Seal) The texture is without sharp edges and disperses easily into the sealers. The lightweight spherical shape and clarity gives Skid Grip™ its specific properties. Produces a “bite” to the concrete surface. Applications include inclined driveways, garages, steps, patios and pool decks. Makes the surface easier to walk on, and will not affect topcoat color.

PACKAGING

Traction Grip™ is available in 16 oz. containers (for five gallons of sealer).

LIMITATIONS

Use with adequate ventilation only. Open windows and doors or use other means to ensure air entering during application and drying. If you experience headaches or dizziness, increase ventilation or wear adequate protection.

DO NOT BACK ROLL WET AREAS!

SHELF LIFE

Shelf life of Traction Grip™ material is approximately 60 months if stored in cool, dry location in original, unopened packaging.

APPLICATION

Add contents of Traction Grip™ to each five-gallon of BRICKFORM Gem-Seal, Gem Cure & Seal, Poly-Seal, and Satin Seal. Mix thoroughly and apply to the surface with a sprayer. Small areas may be brushed. In case of contact with eyes, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, get medical attention immediately.

PRECAUTIONS

It is mandatory to take the following precautions to protect workers and the public:

KEEP OUT OF THE REACH OF CHILDREN.

Keep away from excessive heat and open flame.

Avoid inhalation of vapors. Ensure adequate ventilation.

Avoid contact with skin. Protective clothing is recommended. Contact areas should be thoroughly washed with soap and water.

Avoid contact with eyes. Flush with water if contact occurs.

Avoid ingestion of material. If ingestion occurs, contact a poison control center or physician immediately.

Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet.

Additional Safety Notes:

1. This product is mixed with solvent based sealers.
Do not mix this product in confined areas where sealer vapor can accumulate.
2. Mix outdoors when possible.
3. If indoor mixing is necessary, make sure the building is well ventilated with doors and windows open and fans pushing and/or pulling fresh air in to the area to be sealed (avoid having fans blowing directly on the slab to be sealed). In addition, make sure there is positive air cross flow where the product is mixed. Positive air cross flow can be achieved by placing a fan with adequate airflow 10-15 feet away from the mixing station. Power the fan on and allow the blowing air time to reach the mixing station prior to opening the bucket of sealer. Follow mixing procedures.
4. Ultimate safety can be achieved by using sparkless drills or pneumatic drills with brass fittings to eliminate sparks.
5. Pilot lights should be turned off.

WARRANTY

BRICKFORM a division of Solomon Colors, INC. warrants that these products will be free from defects, and will perform as specified in the Technical Data Sheet, provided that storage, use and application of product are in accordance with manufacturer's recommendations and application instructions. BRICKFORM a division of Solomon Colors, INC. shall not be liable for indirect, incidental, consequential, or special damages, whether due to breach of warranty or tort (including without limitation BRICKFORM a division of Solomon Colors, INC.).

MANUFACTURER

BRICKFORM, A Division of Solomon Colors, Inc.
4050 Color Plant Rd., Springfield, IL 62702