



Material Safety Data Sheet

1. Product and Company Identification

Product Code SR-5
Product Name Strip It™

ManufacturerBRICKFORM, A Division of Solomon Colors, Inc.
Address11061 Jersey Blvd.
City, State, Zip....Rancho Cucamonga, CA 91730

Emergency Phone800-373-7542
Business Phone909-484-3399
Business Fax.....877-857-2615

Last Updated December 1, 2010

NOTICE: THE FOLLOWING INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE AND IS OFFERED IN GOOD FAITH. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

2. HAZARDOUS COMPONENTS

Chemical Name	CAS No.	TLV	%
ETHYL-3-ETHOXYPROPRIONATE	763-69-9	NOT ESTABLISHED	LESS THAN 13%
*N-METHYL-2-PYRROLIDONE	872-50-4	NOT ESTABLISHED	LESS THAN 13%
PROPYLENE GLYCOL MONO-TERT-BUTYL ETHER	57018-52-7	NOT ESTABLISHED	LESS THAN 13%

3. PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 468°F
MELTING POINT: N/A
SOLUBILITY IN WATER: MISCIBLE
VAPOR DENSITY (AIR=1): UNKNOWN
EVAPORATION RATE (BUTYL ACETATE=1): LESS THAN 0.1
VAPOR PRESSURE (@212°F): UNKNOWN
SPECIFIC GRAVITY (WATER=1): 0.91
APPEARANCE/ODOR: LIGHT AMBER/CITRUS SCENT

4. FIRE AND EXPLOSION HAZARDS

FLASH POINT (METHOD USED): 140° F.
FLAMMABLE LIMITS: LOWER EXPLOSION LIMIT = UNKNOWN UPPER EXPLOSION LIMIT = UNKNOWN
EXTINGUISHING MEDIA: WATER FOG OR CARBON DIOXIDE.
SPECIAL FIRE FIGHTING PROCEDURES: NORMAL FOR COMBUSTIBLE LIQUID.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NORMAL FOR COMBUSTIBLE LIQUID.
NFPA RATING: HEALTH=2 FIRE=2 REACTIVITY=0 OTHER: N/A
(0=LEAST HAZARDOUS, 4=MOST HAZARDOUS)

5. REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG ACIDS OR OXIDIZERS, e.g., BLEACH.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE

HAZARDOUS POLYMERIZATION: NONE **CONDITIONS TO AVOID:** N/A

6. HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN? YES INGESTION? YES INHALATION? YES

HEALTH HAZARDS (ACUTE AND CHRONIC): OVEREXPOSURE TO VAPOR CAN CAUSE NARCOSIS, DIZZINESS. EXCESSIVE SKIN CONTACT CAN CAUSE DRYING AND IRRITATION.

CARCINOGENICITY: NTP? NO IARC? NO OSHA? NO

SIGNS AND SYMPTOMS OF EXPOSURE: IF OVEREXPOSED, REDDENING, SWELLING, RASH.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: DERMATITIS, SENSITIVE SKIN, ETC.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: RINSE WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

SKIN: FLUSH WITH COOL RUNNING WATER FOR 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INHALATION: REMOVE TO FRESH AIR.

INGESTION: IF INGESTED, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

7. PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF SPILL: CONTAIN WITH ABSORBANT CLAY, VACUUM OR MOP UP.

WASTE DISPOSAL METHOD: ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.

PRECAUTIONS FOR SAFE HANDLING AND STORAGE: NORMAL FOR COMBUSTIBLE LIQUID. STORE IN COOL AREA.

OTHER PRECAUTIONS: DO NOT MIX WITH OTHER CHEMICALS.

THIS IS A COMMERCIAL PRODUCT, NOT INTENDED FOR HOME USE, KEEP OUT OF REACH OF CHILDREN

8. CONTROL MEASURES

RESPIRATORY PROTECTION: NIOSH-APPR.D RESPIRATOR FOR ORGANIC VAPORS WHEN TLV EXCEEDED

VENTILATION: NORMAL

LOCAL EXHAUST: YES

MECHANICAL (GENERAL): YES

SPECIAL: N/A

PROTECTIVE GLOVES: YES

EYE PROTECTION: YES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WEAR RUBBER BOOTS IF WALKING IN MATERIAL.

WORK/HYGIENIC PRACTICES: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING OR SMOKING.