



SAFETY DATA SHEET

Issue Date 17-Aug-2020

Revision Date 05-Nov-2020

Version 1

BGGSB

Brickform Gem-Guard SB 400

1. IDENTIFICATION

Product identifier

Product Name Brickform Gem-Guard SB 400

Other means of identification

Product Code BGGSB

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier Address

Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Company Phone Number 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

24 Hour Emergency Phone Number 800-373-7542

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This product is classified as hazardous according to the criteria contained in the Hazard Communication Standard 29 CFR 1910.1200 (known as HCS 2012).

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3 (respiratory, central nervous system)
Specific target organ toxicity (repeated exposure)	Category 2 (liver, kidneys, central nervous system)
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements
Causes skin irritation

May cause an allergic skin reaction
Causes serious eye irritation
May cause genetic defects
May cause cancer
May cause respiratory irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor



Appearance Clear to slightly hazy liquid

Physical state Liquid

Odor Aromatic

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment see section 4 of the SDS.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
If skin irritation occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting
In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Keep cool

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Hazards not otherwise classified (HNOC)

Other Information

• Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Tet-Butyl Acetate	540-88-5	20-30	*
Parachlorobenzotrifluoride	98-56-6	20-30	*
Acetone	67-64-1	20-30	*
Acrylic Polymer	Proprietary	10-20	*
Petroleum naphtha, light aromatic	64742-95-6	3-7	*
Trimethylbenzene, Isomers	25551-13-7	3-4.5	*
1,2,4 Trimethylbenzene	95-63-6	2-3	*
Cumene	98-82-8	0.1-0.7	*
Xylenes (o-, m-, p- isomers)	1330-20-7	0.0-0.4	*

*The exact percentage (concentration) of composition has been withheld as a trade secret. This product contains nonhazardous, proprietary alkylsilane and alkylsiloxane. This product also contains trace amounts of benzene (impurity).

4. FIRST AID MEASURES

Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms and effects, both acute and delayed

Symptoms	Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May damage fertility and the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon Dioxide, Foam, Sand. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Keep product and empty container away from heat and sources of ignition. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous combustion products Thermal decomposition can lead to the release of irritating gases and vapors. Carbon oxides.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Keep people away from and upwind of spill/leak. Use personal protection recommended in Section 8. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal. Ground and bond containers when transferring material. Dike to collect large liquid spills.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Never pierce, drill, grind, cut, saw or weld any empty container.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not store near combustible materials. Use spark-proof tools and explosion-proof equipment.

Incompatible materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Tet-Butyl Acetate 540-88-5	STEL: 150 ppm TWA: 50 ppm	TWA: 200 ppm TWA: 950 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m ³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m ³
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F (vacated) TWA: 2.5 mg/m ³	IDLH: 250 mg/m ³ F
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm (vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Trimethylbenzene, Isomers 25551-13-7	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	-
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems. Apply technical measures to comply with occupational exposure limits. However, it is the duty of the user to verify this and follow given exposure limits at the workplace.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles. Avoid contact with eyes.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Aromatic
Appearance	Clear to slightly hazy liquid	Odor threshold	306 ppm
Color	Colorless		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	< -70 °C / -94 °F	
Boiling point / boiling range	56.1 °C / 133 °F	
Flash point	-17.8 °C / 0 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	12.8	
Lower flammability limit:	0.9	
Vapor pressure	26 kPa @20°C	
Vapor density	No information available	
Specific Gravity	No information available	
Water solubility	22.1% w/w	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	18-22 cP	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	< 400 g/L
Density	0.94 g/cc
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Prevent vapor accumulation.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No acute toxicity information is available for this product The product is classified based on the mixture components.
Inhalation	Avoid breathing vapors or mists. May be harmful if inhaled. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin Contact	Prolonged contact may cause redness and irritation. Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance. May cause an allergic skin reaction.
Ingestion	May be harmful if swallowed. Potential for aspiration if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tet-Butyl Acetate 540-88-5	= 4100 mg/kg (Rat)	> 2 g/kg (Rabbit) > 2000 mg/kg (Rabbit)	> 2230 mg/m ³ (Rat) 4 h > 9482 mg/m ³ (Rat) 4 h
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Acrylic Polymer	= 2500 mg/kg (Rat)	-	= 1.71 mg/L (Rat) 4 h
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Trimethylbenzene, Isomers 25551-13-7	= 8970 mg/kg (Rat)	-	-
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	= 39000 mg/m ³ (Rat) 4 h > 3577 ppm (Rat) 6 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms	Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May damage fertility and the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Skin Irritation Cat 2. (based on mixture components). Irritating to skin.
Serious eye damage/eye irritation	Eye Irritation Cat 2. Causes serious eye irritation. (Classification based on mixture components).
Sensitization	May cause sensitization of susceptible persons.
Germ cell mutagenicity	Contains a known or suspected mutagen.
Carcinogenicity	Category 2: Substances that cause cancer in animals, and are considered to cause cancer in man. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Acrylic Polymer	-	Group 3	-	-
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Category 1B. Product is or contains a chemical which is a known or suspected reproductive hazard.

STOT - single exposure STOT SE 3 - Respiratory System. May cause irritation of respiratory tract. May cause dizziness or drowsiness.

STOT - repeated exposure Category 2. (Liver, Kidney, Central Nervous System).

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6452 mg/kg
ATEmix (dermal) 4149 mg/kg
ATEmix (inhalation-dust/mist) 27.0 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Tet-Butyl Acetate 540-88-5	1.38
Parachlorobenzotrifluoride 98-56-6	3.7
Acetone 67-64-1	-0.24
1,2,4 Trimethylbenzene 95-63-6	3.63
Cumene 98-82-8	3.7
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Cumene 98-82-8	Toxic Ignitable
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Emergency Response Guide Number	128

TDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

MEX

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

ICAO (air)

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

IATA

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

IMDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

RID

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

ADR

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0
Cumene - 98-82-8	1.0
Xylenes (o-, m-, p- isomers) - 1330-20-7	1.0

SARA 311/312 Hazard Categories

See section 2 for more information

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Tet-Butyl Acetate 540-88-5	-	-	-	X
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tet-Butyl Acetate 540-88-5	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65

Cumene - 98-82-8	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Tet-Butyl Acetate 540-88-5	X	X	X
Acetone 67-64-1	X	X	X
Parachlorobenzotrifluoride 98-56-6	X	-	-
Trimethylbenzene, Isomers 25551-13-7	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X
Cumene 98-82-8	X	X	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 3	Flammability 3	Reactivity 0	Physical and Chemical Properties -
HMIS	Health hazards 3	Flammability 3	Physical hazards 0	Personal protection X

Prepared By Solomon Colors - Lab Technical Services
Issue Date 17-Aug-2020
Revision Date 05-Nov-2020
Revision Note Initial SDS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet