SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Issuing Date 06-Aug-2025 **Revision Date** 06-Aug-2025 **Version** 1

1. Identification

Product identifier

Product Name Gem Seal 350

Other means of identification

Product Code GS-350

UN/ID no. UN 1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users

Restrictions on use Consumer use

Details of the supplier of the safety data sheet

Supplier Address
Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Manufacturer Address
Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Emergency telephone number

Company Phone Number 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

24 Hour Emergency Phone Number 800-373-7542

Emergency Telephone Hazmat Services 1-800-373-7542

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)
Not applicable

Label elements

Danger

Hazard statements
Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause cancer
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use only non-sparking tools
Take action to prevent static discharges
Use explosion-proof electrical/ ventilating / lighting/ / equipment
Keep cool

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

19.19 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
19.19 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
99.19 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
59.19 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
59.19 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Other Information
May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Mixture

Chemical name	CAS No	Weight-%	Trade secret
Acetone	67-64-1	30-40	*
Petroleum naphtha, light aromatic	64742-95-6	< 10	*
Trimethylbenzene, Isomers	25551-13-7	< 5	*
1,2,4 Trimethylbenzene	95-63-6	< 3	*
Ethylbenzene	100-41-4	< 1	*
Xylene	1330-20-7	< 0.3	*
Cumene	98-82-8	< 0.5	*
Methyl Isopropyl Benzene	25155-15-1	< 0.2	*
Benzene	71-43-2	Trace	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

Inhalation IF exposed or concerned: Get medical advice/attention. Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact Wash skin with soap and water.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms Irritating. May cause redness and tearing of the eyes. Vapors may cause drowsiness and dizziness.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical No information available.

Hazardous combustion products Thermal decomposition can lead to the release of irritating gases and vapors. Carbon monoxide. Carbon dioxide (CO2).

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill; use dry sand to contain the flow of material. Keep out of drains, sewers, ditches and waterways. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with local regulations. Store in accordance with the particular national regulations.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
Trimethylbenzene, Isomers 25551-13-7	TWA: 10 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m³	-
1,2,4 Trimethylbenzene 95-63-6	TWA: 10 ppm	-	TWA: 25 ppm TWA: 125 mg/m³
Ethylbenzene 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³
Xylene 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	-
Cumene 98-82-8	TWA: 5 ppm	TWA: 50 ppm TWA: 245 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m³
Benzene 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm S*	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

Chemical name	ACGIH
Acetone 67-64-1	25 mg/L - urine (Acetone) - end of shift
Ethylbenzene 100-41-4	0.15 g/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift
Xylene 1330-20-7	1.5 g/g creatinine - urine (Methylhippuric acids) - end of shift
Benzene 71-43-2	25 µg/g creatinine - urine (S-Phenylmercapturic acid) - end of shift 500 µg/g creatinine - urine (t,t-Muconic acid) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Clear liquid
Color Colorless
Odor Aromatic / Characteristic
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)		None known
Melting point/freezing point	No data available	None known
Boiling point / boiling range	> 35 °C / 95 °F	estimated
Flash point	< 23 °C / 73.4 °F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known

Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC Content (%)	< 350 g/L
Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents, strong acids, and strong bases.

Hazardous decomposition products Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness. (based on components).

Eye contact Causes serious eye irritation. May cause redness, itching, and pain. (based on components).

Skin contact Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Irritating. May cause redness and tearing of the eyes. Vapors may cause drowsiness and dizziness.

Acute toxicity .

Numerical measures of toxicity
No information available

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	7,774.10 mg/kg
ATEmix (dermal)	5,964.80 mg/kg
ATEmix (inhalation-gas)	> 20,000 ppm
ATEmix (inhalation-vapor)	77.50 mg/l
ATEmix (inhalation-dust/mist)	102.20 mg/l

19.19 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
19.19 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
99.19 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
59.19 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
59.19 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Trimethylbenzene, Isomers 25551-13-7	= 8970 mg/kg (Rat)	-	-
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h
Benzene 71-43-2	= 810 mg/kg (Rat)	> 8200 mg/kg (Rabbit)	= 44.66 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation. Classification based on individual ingredients of the mixture.

Serious eye damage/eye irritation Causes serious eye irritation. Classification based on individual ingredients of the mixture.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity May cause cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-41-4	A3	Group 2B	-	X
Xylene 1330-20-7	-	Group 3	-	-
Cumene 98-82-8	A3	Group 2B	Reasonably Anticipated	X
Benzene 71-43-2	A1	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A1 - Known Human Carcinogen
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone 67-64-1	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
Petroleum naphtha, light aromatic 64742-95-6	-	LC50: =9.22mg/L (96h, Oncorhynchus mykiss)	-	EC50: =6.14mg/L (48h, Daphnia magna)
Trimethylbenzene, Isomers 25551-13-7	-	LC50: =7.72mg/L (96h, Pimephales promelas)	-	-
1,2,4 Trimethylbenzene 95-63-6	-	LC50: 7.19 - 8.28mg/L (96h, Pimephales promelas)	-	EC50: =6.14mg/L (48h, Daphnia magna)
Ethylbenzene 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
Xylene 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas)	EC50 = 0.0084 mg/L 24 h	EC50: =3.82mg/L (48h, water flea)

		LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)		LC50: =0.6mg/L (48h, Gammarus lacustris)
Cumene 98-82-8	EC50: =2.6mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =4.8mg/L (96h, Oncorhynchus mykiss) LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: =5.1mg/L (96h, Poecilia reticulata)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	EC50: =0.6mg/L (48h, Daphnia magna) EC50: 7.9 - 14.1mg/L (48h, Daphnia magna)
Benzene 71-43-2	EC50: =29mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 10.7 - 14.7mg/L (96h, Pimephales promelas) LC50: =5.3mg/L (96h, Oncorhynchus mykiss) LC50: =22.49mg/L (96h, Lepomis macrochirus) LC50: =28.6mg/L (96h, Poecilia reticulata) LC50: 22330 - 41160µg/L (96h, Pimephales promelas) LC50: 70000 - 142000µg/L (96h, Lepomis macrochirus)	-	EC50: 8.76 - 15.6mg/L (48h, Daphnia magna) EC50: =10mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
1,2,4 Trimethylbenzene 95-63-6	3.63
Ethylbenzene 100-41-4	3.6
Xylene	3.15

1330-20-7	
Cumene 98-82-8	3.55
Benzene 71-43-2	2.13

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

UN/ID no.	UN 1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Emergency Response Guide Number	128

TDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II

MEX

UN/ID no.	UN 1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II

ICAO (air)

UN/ID no.	UN 1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II

IATA

UN number or ID number	UN 1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing group	II

IMDG

UN number or ID number	UN 1263
Transport hazard class(es)	3
Packing Group	II

15. Regulatory information

International Inventories

TSCA Complies.

Chemical name	CAS No	US TSCA Inventory listing	US TSCA inactive/active designation
Acetone	67-64-1	Present	Active
Dimethyl carbonate	616-38-6	Present	Active
Petroleum naphtha, light aromatic	64742-95-6	Present	Active
Trimethylbenzene, Isomers	25551-13-7	Present	Active
1,2,4 Trimethylbenzene	95-63-6	Present	Active
Cumene	98-82-8	Present	Active
Xylene	1330-20-7	Present	Active
Methyl Isopropyl Benzene	25155-15-1	Present	Active
Benzene	71-43-2	Present	Active

DSL/NDSL Contact supplier for inventory compliance status.
EINECS/ELINCS Contact supplier for inventory compliance status.
ENCS Contact supplier for inventory compliance status.
IECSC Contact supplier for inventory compliance status.
KECL Contact supplier for inventory compliance status.
PICCS Contact supplier for inventory compliance status.
AIIC Contact supplier for inventory compliance status.
NZIoC Contact supplier for inventory compliance status.

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0
Ethylbenzene - 100-41-4	0.1
Xylene - 1330-20-7	1.0
Cumene - 98-82-8	0.1
Benzene - 71-43-2	0.1

SARA 311/312 Hazard Categories
Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene 100-41-4	1000 lb	X	X	X
Xylene 1330-20-7	100 lb	-	-	X
Benzene 71-43-2	10 lb	X	X	X

CERCLA
This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Benzene 71-43-2	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ

US State Regulations

California Proposition 65
This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Dimethyl carbonate 616-38-6	X	X	X
Trimethylbenzene, Isomers 25551-13-7	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X
Ethylbenzene 100-41-4	X	X	X
Xylene 1330-20-7	X	X	X
Cumene 98-82-8	X	X	X

Methyl Isopropyl Benzene 25155-15-1	X	-	-
Benzene 71-43-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	**Health hazards** 3	**Flammability** 2	**Instability** 0	**Special hazards** -
HMIS	**Health hazards** 3	**Flammability** 2	**Physical hazards** 0	**Personal protection** X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine’s PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Prepared By	Solomon Colors.
Issuing Date	06-Aug-2025
Revision Date	06-Aug-2025
Revision Note	Initial SDS.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.