SAFETY DATA SHEET

Issue Date 16-Apr-2015 **Revision Date** 06-Mar-2023 **Version** 3

MS-100 **Safety Seal 100 VOC**

1. IDENTIFICATION

Product identifier
Product Name Safety Seal 100 VOC

Other means of identification
Product Code MS-100

Recommended use of the chemical and restrictions on use
Recommended Use Restricted to professional users.
Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier Address	**Manufacturer Address**
Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL 62702	Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL 62702

Company Phone Number 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)
24 Hour Emergency Phone Number 800-373-7542

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status
This product is classified as hazardous according to the criteria contained in the Hazard Communication Standard 29 CFR 1910.1200 (known as HCS 2012) and the Hazardous Products Regulations SOR/2015-17 (known as WHMIS 2015).

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements
Causes serious eye irritation
Suspected of causing cancer
May cause respiratory irritation
May cause drowsiness or dizziness
Highly flammable liquid and vapor

Appearance Clear liquid **Physical state** Liquid **Odor** Characteristic

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
In case of fire: Use CO_2, dry chemical, or foam to extinguish

Precautionary Statements - Storage
Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature Mixture.

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	40-60	*
Parachlorobenzotrifluoride	98-56-6	25-35	*
Petroleum distillates, hydrotreated light	64742-47-8	< 2	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye irritation. Suspected of causing cancer. May cause respiratory irritation. May cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media
Water spray (fog). Dry chemical, Carbon Dioxide, Foam, Sand. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical
In the event of fire, cool tanks with water spray.

Hazardous combustion products Thermal decomposition can lead to the release of irritating gases and vapors. Carbon oxides.

Explosion data
Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters
Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation, especially in confined areas.

Other Information ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Ground and bond containers when transferring material. Dike to collect large liquid spills.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Never pierce, drill, grind, cut, saw or weld any empty container.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed in a dry and well-ventilated place. Do not store near combustible materials. Use spark-proof tools and explosion-proof equipment.
Incompatible materials	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines .

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m³ F	TWA: 2.5 mg/m³ F (vacated) TWA: 2.5 mg/m³	IDLH: 250 mg/m³ F

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	Clear liquid	**Odor**	Characteristic
Color	Colorless	**Odor threshold**	No information available

Property	Values	Remarks • Method
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	54.3 °C / 129.7 °F	ASTM D86
Flash point	-17.2 °C / 1 °F	ASTM D56
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	

Vapor density	No information available
Specific Gravity	No information available
Water solubility	Insoluble
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	< 100 g/L
Density	No information available
Bulk density	7-8 lbs/gallon

10. STABILITY AND REACTIVITY

Reactivity
No data available

Chemical stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Conditions to avoid
Extremes of temperature and direct sunlight.

Incompatible materials
Strong oxidizing agents.

Hazardous Decomposition Products
Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No acute toxicity information is available for this product The product is classified based on the mixture components.

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness. Avoid breathing vapors or mists.

Eye contact Irritating to eyes. Avoid contact with eyes.

Skin Contact Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance. Avoid contact with skin and clothing.

Ingestion May be harmful if swallowed. Do not ingest. If swallowed then seek immediate medical assistance.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg (Rat)	> 3300 mg/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Causes eye irritation. Suspected of causing cancer. May cause respiratory irritation. May cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified. (Based on mixture components.).
Serious eye damage/eye irritation Eye Irritation Cat 2. Causes serious eye irritation. (Classification based on mixture components).
Sensitization Not Classified. This product does not contain known sensitizers at levels > or equal to 0.1%.
Germ cell mutagenicity Not classified. (Based on mixture components).
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Parachlorobenzotrifluoride 98-56-6	-	Group 2B	-	X

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans
Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity Not classified. (Based on mixture components).
STOT - single exposure Category 3. May cause irritation of respiratory tract. May cause dizziness or drowsiness.
STOT - repeated exposure Not classified. (Based on mixture components).
Aspiration hazard Not classified. (Based on mixture components).

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) > 5000 mg/kg
ATEmix (dermal) > 5000 mg/kg
ATEmix (inhalation-dust/mist) > 100 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product has not been fully evaluated on the product level.

Persistence and degradability
No information available.

Bioaccumulation
No information available.

Chemical Name	Partition coefficient
Acetone 67-64-1	-0.24
Parachlorobenzotrifluoride 98-56-6	3.7

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Emergency Response Guide Number	128

TDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

MEX

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

ICAO (air)

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

IATA

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

IMDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

RID

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA): This product does not contain chemicals at levels that are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories
See section 2 for more information

CWA (Clean Water Act)
This material, as supplied, does not contain substances that would exceed the reportable quantity as hazardous substances under the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA
This material, as supplied, does not contain substances that would exceed the reportable quantity as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65
This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Parachlorobenzotrifluoride - 98-56-6	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Parachlorobenzotrifluoride 98-56-6	X	-	-
Methyl Methacrylate 80-62-6	X	X	X

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	**Health hazards** 2	**Flammability** 3	**Reactivity** 0	**Physical and Chemical Properties** -
HMIS	**Health hazards** 2	**Flammability** 3	**Physical hazards** 0	**Personal protection** X

Prepared By Solomon Colors
Issue Date 16-Apr-2015
Revision Date 06-Mar-2023
Revision Note
The product composition and classification was revised to reflect the most current composition. All sections of the SDS have been modified since the last revision.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet